

MATERIAL SAFETY DATA SHEET

CLARK OIL AND CHEMICAL
 7555 Bessemer Avenue
 Cleveland, Ohio 44127

Phone: 216 341-8914
 Date Prepared: 5/19/00
 Preparation No: 00053001802

SECTION 1 IDENTIFICATION

PRODUCT NAME: S. G. Type M Rubber Assembly Oil

SECTION 2 HAZARDOUS INGREDIENTS

<u>CHEMICAL NAME / COMMON NAME</u>	<u>% MAX.</u>	<u>TLV or PEL</u>
Petroleum Distillates		5 mg/m ³

SECTION 3 PHYSICAL DATA

APPEARANCE: Transparent amber-green liquid. Mild oil odor.
 SPECIFIC GRAVITY: 0.93
 BOILING POINT: 475°F
 VOLATILE: nil
 SOLUBILITY IN WATER: negligible



SECTION 4 FIRE AND EXPLOSION

FLASH POINT (C.O.C.): 475° F
 FLAMMABLE LIMITS: Unknown
 EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.
 SPECIAL FIRE FIGHTING PROCEDURES: NIOSH/MSHA approved, self contained, pressure demand respirator recommended.
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION 5 HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Oil mist 5mg/m³
 ROUTES OF ENTRY: Eye, skin, inhalation, ingestion.
 ACUTE HEALTH HAZARDS Eyes: Irritation Skin: Irritation Inhalation: Excessive exposure to oil mist may irritate respiratory tract. Ingestion: May irritate gastrointestinal tract or initiate aspiration.
 CHRONIC HEALTH HAZARDS Prolonged/continued skin contact may cause dermatitis, oil mist may irritate respiratory tract.
 MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None listed.
 FIRST AID PROCEDURES:
 EYE: Flush from eyes with copious amounts of water.
 SKIN: Wash with soap and water.
 BREATHING: Move to fresh air.
 INGESTION: Do not induce vomiting due to danger of aspirating fluid into lungs.
 CARCINOGENICITY: Components of this product are not listed as carcinogens by NTP, IARC Monographs, or OSHA.

SECTION 6 REACTIVITY DATA

STABILITY: Stable

MATERIAL SAFETY DATA SHEET

HAZARDOUS POLYMERIZATION: Will not occur.
 INCOMPATIBILITY: Avoid contact with strong oxidizers.
 HAZARDOUS DECOMPOSITION PRODUCTS and PRODUCTS OF COMBUSTION: Oxides of carbon; smoke.

SECTION 7 SPILL OR LEAK PROCEDURE

STEPS TO BE TAKEN IN CASE OF LEAK OR SPILL: Contain spill, stop source of leak, pump spilled material into salvage container, soak up remaining material with absorbant such as sand or clay. Prevent product from entering potable or natural water systems.
 WASTE DISPOSAL METHOD: Dispose of in accordance with all applicable federal, state and local regulations.

SECTION 8 SPECIAL PROTECTION INFORMATION

EYE PROTECTION: Splash protection.
 PROTECTIVE GLOVES: Oil resistant gloves.
 RESPIRATORY PROTECTION: NIOSH/MSHA approved respirator recommended if oil mist TLV is exceeded.
 VENTILATION: Recommended to maintain oil mist below TLV limit.
 OTHER PROTECTION: As necessary to prevent prolonged skin contact.

SECTION 9 SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Store away from direct heat source and strong oxidizing agents. Launder contaminated clothing before reuse.
 OTHER PRECAUTIONS: Do not pressurize, cut, weld, braze, drill, grind or heat empty drums as some flammable, hazardous or combustible residue may be present. Avoid breathing oil mist. For industrial use only.

SECTION 10 ADDITIONAL INFORMATION

TSCA: The components of this product are listed on the EPA/TSCA Chemical Substances Inventory.

HMS RATING:

HEALTH:	
FLAMMABILITY:	1
REACTIVITY:	0
PERSONAL PROTECTION:	B

N.A. = Not Applicable
 N.D. = Not Determined
 N.L. = Not Listed

TLV = Threshold Limit Value (ACGIH)
 PEL = Permissible Exposure Limit (OSHA)